



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordinator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



Panoramic Dental X-Ray PLANMECA PRO ONE (Reconditioned)

- Used,
- Technical condition: very good,
- Visual condition: very good,
- Manufactured in Finland,
- Power supply: 230 V,
- Frequency: 50/60 Hz,
- Power: 850 W,
- Planmeca ProOne is a full-featured unit for panoramic imaging. It was designed with simplicity in mind, but also features several innovative features, thus combining extensive diagnostic capabilities with excellent image quality,
- Compact and easy to use,
- Modern styling and extremely lightweight design, at 69 kg,
- Unit features:
 - Helpful user interface - graphical, touch-screen display allows easy and quick selection of the full range of offered exposures and X-ray image parameters,
 - Selectable menu in the following languages: PL, EN, FR, SV, DE, IT, FI, DA,
 - Easy Patient Positioning - Open patient positioning and side access minimize the risk of errors due to improper patient positioning, allowing the patient to be monitored freely from the front and side. Side access is a great convenience for all patients, whether standing or sitting. Positioning is assisted by a triple laser beam system that indicates the correct anatomical points for positioning,
 - Autofocus function - automatically sets the focal layer using a low-dose preview image of the patient's central incisors. A perfect panoramic image every time,
- Imaging programs:
 - Standard panoramic program,
 - TMJ lateral,
 - TMJ PA,
 - PA sinus program,
 - Child (pediatric) mode available for each program to reduce dose,
 - All images taken are available immediately on the monitor screen, without the need for film, reagents or a developer. An added advantage is that they can be digitally processed using ROMEXIS software,
- Specifications:
 - X-ray tube: D-058SBR,
 - Focal size: 0.5 x 0.5 mm (IEC 336)
 - SID: 480 mm (19 in.),
 - Total filtration: equivalent of min. 2.5 mm Al,
 - Anode voltage: 60 - 70 kV,
 - Anode current: 2 - 7 mA DC,
 - Exposure time: 2 - 10 s,
 - Chin support level: 95 - 178 cm (37.4 - 70 in.),
- The set includes:
 - NEC MultiSync EA244WMI monitor,
 - Dell computer,
 - Mouse and keyboard,
 - Instruction Set,
 - Planmeca Romexis Software for Windows/Mac Os - CD,
 - Sensor calibration software,
 - Device accessory kit (chins, teathers, etc.),
 - Wired remote control,
- Space required: 103 x 74 x 233 cm,
- Overall dimensions: 85 x 45 x 186 cm,
- Weight of the device: 69 kg,
- Valid technical passport issued,
- Warranty:
 - 6 months for domestic market - Poland,
 - 3 month for the international market,
- Possibility of financing (Poland only): Installments, Leasing, Loan,

If you have any questions, please do not hesitate to contact us!

In case you don't find the product you are interested in, please get in touch with us and we will do our best to find the perfect solution for YOU.

WE SPEAK ENGLISH

HABLAMOS ESPANOL

WIR SPRECHEN DEUTSCH

ON PARLE FRANCAIS

WIJ SPREKEN DUTCH

Мы говорим по русски

Мы говорим по украински

