



**PRAISTON Sp. z o.o.**  
ul. Górowska 32  
64-100 Leszno  
Polska

Biuro: +48 65 527 01 67  
Serwis: +48 782 844 000  
Fax: +48 65 527 01 67

E-mail: [biuro@praiston.pl](mailto:biuro@praiston.pl)

Koordinator ds. sprzedaży  
Krzysztof Wybieralski  
+48 882 762 006

[kw@praiston.pl](mailto:kw@praiston.pl)



## **AJL LW 102 Analogue water bath (Reconditioned)**

- Reconditioned (used),
- Technical condition: very good,
- Visual condition: very good,
- Real photographs of the product,
- Made in Poland,
- Power supply: 230 V,
- Frequency: 50/60 Hz,
- Power: 1000 W,
- Analogue water bath LW 102 - is designed for analytic-medical, microbiological, physical, chemical and other studies that require strict temperature regimes, especially those in which the possibility of controlling processes occurring in samples during studies is required. The LW bath thermostat is equipped with a stirrer that guarantees uniform temperature distribution throughout the tank. The bath can be fitted with a cooling element which, when connected to an external water supply, allows the desired temperature to be maintained below ambient,
- The constant water temperature, maintained by a thermostat in the tank, can be regulated in two ways:
  - Smoothly by means of two controllers, one for coarse control and the other for fine control (it is necessary to control the temperature by means of an external thermometer),
  - Fixed by a switch to one of four quantities (no external temperature control is needed),
- Specifications:
  - Temperature range continuously adjustable from 20°C to 60°C,
  - Fixed temperatures 25°C, 30°C, 37°C, 56°C,
  - Temperature stabilisation accuracy  $\pm 0.1^\circ\text{C}$ ,
  - Water heating time to 56°C 20 min,
  - Cooling from external water supply,
  - Rotary agitator 1100 rpm,
  - Visual signalling:
    - Water heating,
    - Reaching the set temperature,
    - Exceeding the set temperature,
    - Low water level at the same time with heating lock,
  - Acoustic signalling:
    - Alarm of exceeding the set temperature by 1°C,
    - Alarm when the water level falls below the minimum,
  - Minimum temperature difference between ambient and set temperature:
    - 0°C with external cooling,
    - 5°C without external cooling,
- Included:
  - Stainless steel container with dimensions: 30 x 15 x 16 cm,
  - Power cord,
- Overall dimensions: 36 x 21 x 32 cm
- Weight: 5.5 kg,
- Valid technical passport issued,
- Warranty:
  - 6 months for the domestic market - Poland,
  - 3 months for the international market,
- Possibility of financing (Poland only): Instalments, Leasing, Loan,

If you have any questions, please do not hesitate to contact us!

In case you don't find the product you are interested in, please get in touch with us and we will do our best to find the perfect solution for YOU.

WE SPEAK ENGLISH

HABLAMOS ESPANOL

WIR SPRECHEN DEUTSCH

ON PARLE FRANCAIS

WIJ SPREKEN DUTCH

Мы говорим по русски

Мы говорим по украински

