



**PRAISTON Sp. z o.o.**  
ul. Górowska 32  
64-100 Leszno  
Polska

Biuro: +48 65 527 01 67  
Serwis: +48 782 844 000  
Fax: +48 65 527 01 67  
E-mail: [biuro@praiston.pl](mailto:biuro@praiston.pl)

Koordinator ds. sprzedaży  
Krzysztof Wybieralski  
+48 882 762 006  
[kw@praiston.pl](mailto:kw@praiston.pl)



## **GE DATEX-OHMEDA N-MRI2-01 patient's monitor/cardiac monitor (Reconditioned)**

- Reconditioned (used),
- Technical condition: very good,
- Visual condition: very good,
- **Real photos of the product,**
- Made in the USA,
- Power supply: 230 V and via in-built Ni-MH battery,
- Frequency: 50/60 Hz,
- Power: 140 VA,
- **GE Datex-Ohmeda N-MRI2-01** is a patient monitor built in an aluminum Faraday protection cage, suitable for use in an MRI environment,
- It is characterized by the possibility of multiple measurement modules at the same time and the display of measured data on a diagonal color LCD screen: 12,1",
- ComWheel navigation dial operation for easy information entry and screen navigation,
- **Menu to be chosen in English and French,**
- **French keyboard on the control panel,**
- Custom display options allow viewing and analysis of data in graphical and numerical formats, compilation of real-time measurements and trends, and any configuration of each screen element - from curves to parameter names,
- Audible and visual alarms,
- M-OSAT TruTrak characteristics - is a proprietary technique for greater SPO2 performance. High data sampling rate, identification, quantitative analysis and motion correction allows tracking patient saturations under clinical motion conditions,
- **Equipped with:**
  - PCMCIA memory card reader (card not included),
  - Fiber optic ports: Y, X, B, G, R,
  - Sockets:
    - Mini DIN (X1),
    - DIN X - 2 pieces. - (X2, X3),
  - Data transmission channels RX i TX,
  - **Modules with wiring:**
    - ECG - 3 - lead cable (suitable for MRI),
    - NIBP - Size 23 - 33 cm 2 - vein cuff with air tubing,
    - SPO2 - GE OxyTip+ MRI Clip Sensor with cable (suitable for MRI) - can be added at extra cost to the SPO2 sensor for children shown in the last photo,
    - IBP x 2 - Adapter (splitter for two outputs + connecting cables), no disposable transducers (can be added at extra cost),
    - M-CAIO anesthetic gas measurement module (sevoflurane, halothane, isoflurane, enflurane, desflurane) O2, N2O, CO2, with D-Fend water trap,
- **The monitor is placed on a mobile table equipped with a:**
  - Built-in drawer for MRI-compatible small items with dimensions: 23.5 x 12.5 x 23.5 cm,
  - Built-in cabinet with shelf, dimensions: 20 x 24 x 46 cm,
  - On four wheels with brakes,
- **In the set:**
  - German instruction manual (PDF),
  - Power cord,
- Dimensions:
  - Overall: 56,5 x 57 x 148,5 cm,
  - Of the monitor: 30 x 45 x 36,5 cm,
- Set's weight: 57,5 kg,
- Cat 02,
- **It has up-to-date overview and is ready to operate,**
- **Provided with a 12-month valid Technical Passport (Service Report),**
- **Guarantee:**
  - **6 months for the domestic market (Poland),**
  - **3 months for the international market,**
  - **Possible guarantee extension for extra fee, up to 12 months for both, domestic and international market,**
- Financing possibilities (Poland only): Installments, leasing, loan,

