



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



NBVE 60/30 P germicidal lamp (New)

- A brand new product,
- Made in Poland,
- It has a PZH certificate (National Institute of Hygiene),
- NBVE 60/30 P dual-purpose flow germicidal lamp without timer,
- The use of energy-saving flow bactericidal and virucidal lamps of the NBVE series is one of the most effective methods of disinfection,
- This device can be used in two ways: when patients and staff are inside (then the airflow function of the lamp is used, and thus the biocidal UV-C radiation does not escape) or when no one is in the room,
- In this case, external irradiators are activated, which emit radiation with a wavelength of 253 nm into the environment, and thus effectively inactivate mold, bacteria, viruses, fungi and any other microorganisms from the irradiated surfaces,
- **Suitable for:**
 - Hospitals (surgery units, treatment rooms, emergency rooms, patients' wards, isolation rooms, A&E places, dirty linen rooms),
 - Clinics (doctor's and treatment rooms),
 - Laboratories,
 - Pharmacies,
 - The following industries: pharmaceutical, food-processing, cosmetics,
 - Hotel industry and gastronomy,
- **Advantages of NBVE 60/30 P germicidal lamp:**
 - Mounting type: M – mobile, on a tripod,
 - The highest quality of this device is confirmed by all required certificates,
 - Application: in waiting rooms, emergency rooms, operating rooms, laboratories, corridors, nurseries and kindergartens, and in all places where there are many people and where strict sterility is required,
 - The acid-resistant sheet metal used in the manufacturing process of the case increases the disinfecting properties of the lamp,
 - Energy-saving model: using this lamp is very economical - it saves up to 300 zlotys per month,
 - The device has two radiators: the external one allows disinfection of the entire room during the absence of the users of the room/office; the internal one allows effective deactivation of viruses, fungi, mold and other microorganisms even during the operation of the office (i.e. when the staff and patients are in the room),
 - Forced airflow through the UV-C chamber ensures that the harmful radiation emitted by the internal emitters does not escape to the outside,
 - The device has passed specialized tests in a microbiological laboratory,
 - When using this dual-function germicidal flow lamp, a consistently high level of air disinfection is guaranteed ,
- **Technical data:**
 - A mobile lamp, on a tripod,
 - Supply voltage: 230 V 50 Hz,
 - Power consumption: 115 W,
 - Internal UV-C emitting element: 2 x 30W,
 - External UV-C emitting element: 1 x 30W,
 - UV-C irradiance at 1 m distance: 100 µW/cm²,
 - Radiant life: 9000 h,
 - Fan capacity: 132 m³/h,
 - Disinfected volume: 25 - 50 m³,
 - Operating range of the lamp: 10 - 20 m²,
 - Anti-schock safety class: I,
 - Case type: IP 20,
 - Chamber's dimensions: 1125 x 285 x 130 mm,
 - Dimensions: 600 x 1270 x 600 mm,
 - Masa: 13 kg,
- It has a valid Technical Passport,
- Guarantee: 12 months,

