



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordinator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



NBVE 110/55 P germicidal lamp (New)

- A brand new product,
- Made in Poland,
- It has a PZH certificate (National Institute of Hygiene),
- NBVE 110/55 P dual-purpose flow germicidal lamp without timer,
- The use of energy-saving flow bactericidal and virucidal lamps of the NBVE series is one of the most effective methods of disinfection,
- This device can be used in two ways: when patients and staff are inside (then the airflow function of the lamp is used, and thus the biocidal UV-C radiation does not escape) or when no one is in the room,
- In this case, external irradiators are activated, which emit radiation with a wavelength of 253 nm into the environment, and thus effectively inactivate mold, bacteria, viruses, fungi and any other microorganisms from the irradiated surfaces,
- **Suitable for:**
 - Hospitals (surgery units, treatment rooms, emergency rooms, patients' wards, isolation rooms, A&E places, dirty linen rooms),
 - Clinics (doctor's and treatment rooms),
 - Laboratories,
 - Pharmacies,
 - The following industries: pharmaceutical, food-processing, cosmetics,
 - Hotel industry and gastronomy,
- **Advantages of NBVE 110/55 P germicidal lamp:**
 - Mounting type: M - mobile, on a tripod,
 - Application: operating rooms, hospitals, laboratories, clinics, emergency rooms, kindergartens, nurseries, hotels, production halls, waiting rooms, corridors and other places where there are many people every day,
 - The lamp allows a significant reduction in electricity consumption (energy-saving properties),
 - Acid-resistant sheet metal case increases the disinfecting properties of the device, also helps to keep it clean,
 - Guarantee of constant and high level of air disinfection,
 - Tests conducted in a professional microbiological laboratory confirm the effectiveness of the device,
 - The highest quality is also confirmed by certificates,
 - External direct-acting radiator allows disinfection of the entire room during the absence of the users of the room/office,
 - Internal radiators, allow the device to be activated while staff and patients are inside,
 - Forced airflow through the UV-C chamber,
- **Technical data:**
 - A mobile lamp, on a tripod,
 - Supply voltage: 230 V 50 Hz,
 - Power consumption: 145 W,
 - Internal UV-C emitting element: 2 x 55W,
 - External UV-C emitting element: 1 x 55W,
 - UV-C irradiance at 1 m distance: 150 μ W/cm²,
 - Radiant life: 9000 h,
 - Fan capacity: 199 m³/h,
 - Disinfected volume: 45 - 90 m³,
 - Operating range of the lamp: 18 - 36 m²,
 - Anti-schock safety class: I,
 - Case type: IP 20,
 - Chamber's dimensions: 1125 x 285 x 130 mm,
 - Dimensions: 600 x 1270 x 600 mm,
 - Weight: 13,5 kg,
- It has a valid Technical Passport,
- Guarantee: 12 months,

