



**PRAISTON Sp. z o.o.**  
ul. Górowska 32  
64-100 Leszno  
Polska

Biuro: +48 65 527 01 67  
Serwis: +48 782 844 000  
Fax: +48 65 527 01 67

E-mail: [biuro@praiston.pl](mailto:biuro@praiston.pl)

Koordinator ds. sprzedaży  
Krzysztof Wybieralski  
+48 882 762 006

[kw@praiston.pl](mailto:kw@praiston.pl)



**GE CARESCAPE B650 patient's monitor/cardiomonitor (Reconditioned)**

- Reconditioned (used),
- Technical condition: very good,
- Visual condition: very good,
- **Real product photos,**
- Made in the USA (2012)
- Power supply: 230V,
- Battery power supply: via a new built-in lithium-ion battery 11.1V 6.21 Ah - **(the battery can be replaced with a new one for an additional fee),**
- Frequency: 50/60 Hz,
- **CARESCAPE B650** is designed to make care more efficient. It helps manage patient flow by providing clinicians with the right clinical information when and where they need it. Its intuitive design makes it easy to train staff of all experience levels, and its upgradeability protects your investment for the long term.
- Combining the best of Marquette® Electronics and Datex-Ohmeda® monitor solutions on one platform,
- Advanced measurement modules offer a wide range of clinical measurements,
- CARESCAPE PDM Patient Data Module provides consistent hemodynamic monitoring during intra-hospital transport and trend data transfer,
- Innovative algorithms and solutions such as GE EK-Pro, GE DINAMAP® and the 12SL™ diagnostic ECG recording system with direct bidirectional connectivity to the MUSE® system help to make accurate diagnoses,
- Advanced respiratory gas modules provide complete respiratory monitoring with gas exchange measurements,
- Various parameters help assess the adequacy of anesthesia in the operating room, and in the intensive care unit they facilitate the decision to wean the patient from the ventilator,
- The ability to connect to Aware® Gateway allows for connectivity to medical data collection systems using the standard HL7 protocol,
- The Pages and Profiles feature can increase the versatility and efficiency of patient management by allowing you to configure monitors to meet department standards and patient populations,
- User-selectable display modes allow for presentation of 8 to 14 waveforms with screen overlays and fields, allowing the screen to be tailored to the needs of staff and patients,
- Auto View on Alarm (AVOA) enables automatic distribution of high priority alarms within the department,
- Built-in USB ports allow you to connect a keyboard, mouse, barcode reader and other data entry devices,
- The Trim Knob® and touchscreen or hardware buttons allow you to easily use basic functions,
- Dedicated software and parameters for anesthesia, postoperative, intensive care and neonatal intensive care make it easy to configure the monitor to meet specific clinical needs,
- The ergonomic, compact design with a rotating module frame allows it to be adapted to various clinical environments and can be modified with multi-parameter modules and other options,
- **Display:**
  - Dimensions: 15 inches,
  - Type: Color LCD screen with active matrix technology,
  - Resolution: 1024 x 768 pixels (XGA),
  - Number of passes: 8 single, up to 14 with overlays and windows,
  - Plotting speed: 0.625, 6.25, 12.5, 25, 50 mm/s
  - Configuration: Automatic configuration based on available parameters. Manual configuration of up to 8 user-configurable profiles covering specific clinical configurations and up to 6 user-configurable screen pages for each profile,
- **Controls:** Navigation knob, touch **screen** , hardware **buttons** ,
- **It has the following modules:**
  - **PDM:**
    - ECG: 3,7 and 12 lead ECG with 3,5,6 and 10 wires,
    - SpO2: Masimo SET, Nellcor OxiMax,
    - NIBP: GE DINAMAP SuperSTAT algorithm,
    - InvBP: 0 or 4,
    - Temperature: 2, optionally with CO
    - Cardiac output: optionally with temperature,
  - **E-CAIOV:** CO2, O2, N2O, anesthetics, spirometric measurements,
- Monitor mounted on a mobile cart with a 5-arm base on wheels, two of which have a brake, a basket for accessories and a transport handle,
- **Possibility to select menu language: PL, EN, CZ, DK, FR, DE, ES, HU, CN, JP, PR, RU, IT, FN,**
- **Included in the set:**
  - English user manual (PDF),
  - NELLCOR OxiMax SPo2 sensor,
  - New 25-35 cm cuff for blood pressure measurement + extension cord,
  - ECG cable – 3 lead,
  - Power cord,
- Dimensions: 50 x 60 x 144 cm,
- Weight: 30 kg,
- **It has a current inspection and is ready to work,**
- **Issued Technical Passport (Service Report) valid for 12 months,**
- **Guarantee:**
  - **6 months for domestic market (Poland),**
  - **3 months to international market,**
  - **Possibility of extending the warranty for an additional fee to 12 months for the domestic and international market,**
- Financing options (Poland only): Installments, Leasing, Loan,

