

PRAISTON Sp. z o.o. ul. Górowska 32 64-100 Leszno Polska Biuro: +48 65 527 01 67 Serwis:+48 782 844 000 Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży Krzysztof Wybieralski +48 882 762 006

kw@praiston.pl



RODENSTOCK RSL 5000 Slit lamp (New)

- New,
- Made in Germany,
- Advantages and features of the RSL 5000 Slit Lamp:
 - · Haag-Streit (top-light) type lamp,
 - · LED illumination,
 - · Stereomicroscope with five magnification ranges,
 - Exceptional optical quality,
 - · Converging binocular microscope,
 - 5-stage magnification adjustment,
 - · Extensive set of filters and accessories,
- Technical specifications:
 - Microscope:
 - Version with five magnifications,
 - 12.5x magnification eyepiece,
 - Total magnification factor: x6, x10, x16, x25, x40,
 - Pupil spacing: 49 to 77 mm,
 - Focal distance: 107 mm,
 - Field of view: 34, 22, 14, 8.5, 5.5 mm,
 - Convergence angle: 13°,
 - Slit illumination:
 - Slit width: 0-12 mm infinitely adjustable,
 - Slot length: 12 mm (1.0-12 mm continuously adjustable),
 - Hole diameters: 0.2, 1 mm square, 2, 3, 5, 9, 12 mm,
 - Filters: heat absorption filter, blue filter, red-free filter,
 - Slit angle: +/- 90° continuous,
 - Slit rotation: +/- 90° with reference scale,
 - Fixation lamp: LED,
 - Light source: LED / 12V,
 - Additional features (at extra charge):
 - Additional diffuser,
 - Yellow filter integrated into the microscope,
 - TAT-100R applanation tonometer,
- · Dimension and weight:
 - Dimension (WDH): 350 x 410 x 702 mm,
- Weight: 21 kg,
- Power requirements:
 - Power supply: (100-240 V input) +/- 10% multi-plug complying with EN 60601-1, EN 61000-6-2, EN 61000-6-3,
- Power supply: 12V DC / 2.5 A IEC / EN 60 6001,
- It has a current Technical Passport issued,
- Warranty 12 months,







www.praiston.pl 2022