



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordinator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



PHILIPS HEARTSTART XL+ Defibrillator (Reconditioned)

- Reconditioned (used),
- Technical condition: very good,
- Visual condition: very good,
- Real photos of the product,
- Manufactured in , (2014),
- Power supply: 230 V,
- Battery power: via lithium-ion battery 14.8V 6.6 Ah, 98 Wh - no battery included (can be retrofitted with a new one at additional cost),
- Frequency: 50/60 Hz,
- Menu in language: ENG,
- The Philips HeartStart XL+ defibrillator offers advanced and basic life support functions , which are contained in a compact, lightweight and easy-to-use device. The XL+ provides resuscitation and emergency teams with many innovations to help them respond confidently and efficiently to patients in the hospital environment. It provides four clinical modes of operation: monitor, manual defibrillation, AED and pacemaker (optional). The AC adapter can serve as an additional power source and provides continuous battery charging. The XL+ regularly performs automatic tests and stores critical event and trend data in its internal memory,
- Monitoring mode allows simultaneous monitoring of up to three ECG curves, obtained with a set of 3- or 5-lead ECGs or multifunctional electrodes,
- Manual defibrillation mode offers simple 3-step defibrillation. It analyzes the patient's ECG and selects and sets the energy as needed,
- AED mode analyzes the patient's ECG and determines whether a shock is recommended,
- Pace mode offers non-invasive transcutaneous pacing,
- Specifications:
 - Defibrillation energy (J): 1; 2; 3; 4; 5; 6; 7; 8; 9; 10; 15; 20; 30; 50; 70; 100; 120; 150; 170; 200,
 - Waveform: two-phase truncated exponential. Waveform parameters adjusted as a function of patient impedance,
 - Shock Series: configurable energy escalation in series,
 - Charging time: from 3 to 17 seconds,
 - Patient impedance range: from 25 to 250 ohms,
 - AC power supply,
 - Operating mode: manual semi-automatic,
 - Number of ECG leads: 3,
 - Children defibrillation,
 - Internal defibrillation,
 - Screen: TFT LCD,
 - Screen diagonal: 6.5 inches,
 - Printer:
 - Continuous ECG strip: Print button starts and stops the strip. The printer can be configured to run in real time or with a 10-second delay. The strip prints the main ECG lead and second waveform with event annotations and measurements,
 - Automatic printing: the printer can be configured to automatically print on event annotation, charging, shock and alarm,
 - Speed: 25 mm/sec: With an accuracy of $\pm 5\%$,
 - Amplitude accuracy: 5% for offset voltages ± 300 mV at 5 Hz,
 - Paper size: 50 mm wide,
- Included:
 - User manual in English(PDF),
 - ECG 3-lead cable,
 - AED cable,
 - Test Plug,
 - Power cord,
- Dimensions: 23 x 30 x 28 cm,
- Weight: 8kg,
- Cat D 127,
- Has a current inspection and is ready for operation,
- Issued Technical Passport (Service Report) valid for 12 months,
- Warranty:
 - 6-months for domestic market (Poland),
 - 3-months for the international market,
 - Possibility to extend the warranty up to 12 months for domestic and international markets for a surcharge,
- Possibility of financing (Poland only): Installments, Leasing, Loan,

If you have any questions, please do not hesitate to contact us!

In case you don't find the product you are interested in, please get in touch with us and we will do our best to find the perfect solution for YOU.

