



**PRAISTON Sp. z o.o.**  
ul. Górowska 32  
64-100 Leszno  
Polska

Biuro: +48 65 527 01 67  
Serwis: +48 782 844 000  
Fax: +48 65 527 01 67

E-mail: [biuro@praiston.pl](mailto:biuro@praiston.pl)

Koordynator ds. sprzedaży  
Krzysztof Wybieralski  
+48 882 762 006

[kw@praiston.pl](mailto:kw@praiston.pl)



## **TIC MEDIZINTECHNIK GALILEO Urodynamics measuring station with video function (New)**

- New,
- Made in Germany,
- Galileo is a urological diagnostic device for determining specific physiological parameters in the lower urinary tract in men and women. Typical applications include studies of bladder emptying disorders and various forms of incontinence,
- Product features and advantages:
  - Efficient and convenient data management system,
  - Analysis at the touch of a button,
  - Integration with existing clinical information systems and networks,
  - Made of high quality components,
  - Flow transducer with height-adjustable stand, with wireless capability (optional),
  - 2 flow channels (second optional) and 2 EMG channels (second optional),
  - High sampling rate for precise measurement results,
  - Easily accessible USB ports,
  - Wireless remote control for easy operation (two-way communication),
  - Easy-to-use roller pump for accurate filling,
  - Isolation transformer and additional galvanic isolation for maximum patient safety,
  - Puller (puller) for best catheter positioning,
  - Printer for standard paper size (A4),
- The station allows the following tests to be performed:
  - Cystometry, filling phase of cystometry,
  - Cystometry, evacuation phase of cystometry (pressure and flow measurement),
  - Compliance (displacement ratio),
  - Pressure flow measurement,
  - ICS, CHESS, linear PURR,
  - Urethral pressure profile at rest,
  - Urethral pressure profile under load,
  - Transmission / depression / and urethral closure pressure, depression quotient, transmission coefficient,
  - Uroflow with parallel EMG display,
  - Siroky et al, Höfner Index,
- Specifications:
  - Number of pressure channels: 4,
  - Number of flow channels: 2 (second optional),
  - Number of EMG channels: 2 (second optional),
  - Input/output: 22"-TFT-monitor, printer, mouse, keyboard, RF remote control,
  - Patient safety: isolation transformer, galvanic isolation,
  - Interfaces: LAN, USB, GDT (optional), HL7 (optional), DICOM (optional),
  - SQL-based database for statistical purposes,
- Has a current Technical Passport issued,
- Warranty 24 months,

If you have any questions, please do not hesitate to contact us!

In case you don't find the product you are interested in, please get in touch with us and we will do our best to find the perfect solution for YOU.

