



**PRAISTON Sp. z o.o.**  
ul. Górowska 32  
64-100 Leszno  
Polska

Biuro: +48 65 527 01 67  
Serwis: +48 782 844 000  
Fax: +48 65 527 01 67

E-mail: [biuro@praiston.pl](mailto:biuro@praiston.pl)

Koordinator ds. sprzedaży  
Krzysztof Wybieralski  
+48 882 762 006

[kw@praiston.pl](mailto:kw@praiston.pl)



## **GE CARESCAPE B650 Patient monitor / cardiac monitor (Reconditioned)**

- Reconditioned (used),
- Technical condition: very good,
- Visual condition: very good,
- Real photos of the product,
- Made in Finland, (2015),
- Power supply: 230 V,
- Emergency power supply: via 1 built-in 11.1 V 6.21 Ah battery -possible to replace with a new one at additional cost,
- Frequency: 50/60 Hz,
- CARESCAPE B650 is designed for more efficient medical care. It helps manage patient flow, providing clinicians with the right clinical information when and where they need it. Its intuitive design makes it easy to train staff at all levels of experience, and its upgradeability protects your investment for the long term,
- Combines the best of Marquette® Electronics and Datex-Ohmeda® monitors on a single platform,
- Advanced measurement modules offer a wide range of clinical measurements,
- CARESCAPE PDM patient data module provides consistent hemodynamic monitoring during in-hospital transport and trend data transfer,
- Innovative algorithms and solutions such as GE EK-Pro and GE DINAMAP® and the 12SL™ Diagnostic ECG System with direct two-way connectivity to the MUSE® system help make accurate diagnoses,
- Advanced respiratory gas modules provide complete respiratory monitoring with gas exchange measurements,
- A variety of parameters help assess the adequacy of anesthesia in the operating room, and in the intensive care unit facilitate decisions about weaning the patient from the ventilator,
- The ability to connect to the Aware® Gateway allows connectivity to systems that collect medical data using the standard HL7 protocol,
- "Pages and Profiles" feature can increase the versatility and efficiency of patient management by allowing monitors to be configured for departmental standards and patient populations,
- User-selectable display modes allow presentation of 8 to 14 curves with screen overlays and fields, allowing the screen to be customized according to staff and patient needs,
- Auto View on Alarm (AVOA) function enables automatic distribution of high-priority alarms within the department,
- Built-in USB ports allow connection of a keyboard, mouse, barcode reader and other data entry devices,
- Trim Knob® and touchscreen or hardware buttons allow easy use of basic functions,
- Dedicated software and parameters for anesthesia, post-operative, intensive care and neonatal intensive care units make it easy to configure the monitor for specific clinical needs,
- Taking ergonomic principles into account, the compact design with a swivel module frame allows it to fit into a variety of clinical environments and allows modification with multi-parameter modules and other options
- Taking ergonomic principles into account, the compact design with a rotating module frame allows it to fit into a variety of clinical environments and allows modification with multi-parameter modules and other options,
- Display:
  - Dimensions: 15 in,
  - Type: Color liquid crystal screen with active matrix technology,
  - Resolution: 1024 x 768 pixels (XGA),
  - Number of waveforms: 8 single, up to 14 with overlays and windows,
  - Drawing speed: 0.625, 6.25, 12.5, 25, 50 mm/sec,
  - Configuration: Automatic configuration with available parameters. Manual configuration of up to 8 user-configurable profiles covering specific clinical configurations and up to 6 user-configurable screen pages for each profile,
- Controls: navigation dial, touch screen, hardware buttons,
- Features the following modules:
  - E-PSMP-01:
    - ECG: 3,7 and 12 leads ECG with 3,5,6 and 10 leads,
    - SpO2: GE SpO2,
    - NIBP: GE
    - InvBP: 0 or 2,
    - Temperature: 2,
  - E-CAiO: CO2, O2, N2O, anesthetics,
- Selectable menu in CN, CS, DU, NL, EN, FN, FR, GR, HU, IT, JP, NR, PL, PT, RU, ES, SE,
- Included:
  - User manual in English(PDF),
  - SPo2 sensor,
  - NiBP pressure cuff + extension cable,
  - ECG cable - 3 lead,
  - Power cord,
- Dimensions:
  - Overall: 40 x 22 x 32 cm,
- Weight: 12 kg,
- Cat 03,
- Has a current inspection and is ready for operation,
- Issued Technical Passport (Service Report) valid for a period of 12 months,
- Warranty:
  - 6-months for the domestic market (Poland),
  - 3-months for the international market,
  - Possibility to extend the warranty up to 12-months for domestic and international markets for a surcharge,
- Possibility of financing (Poland only): Installments, Leasing, Loan,

If you have any questions, please do not hesitate to contact us!

In case you don't find the product you are interested in, please get in touch with us and we will do our best to find the perfect solution for YOU.

