



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordinator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



MEDRAD MARK V PRO VIS Injection system (Reconditioned)

- Reconditioned (used),
- Technical condition: very good,
- Visual condition: very good,
- Real photos of the product,
- Made in the USA,
- Power supply: 230 V,
- Frequency: 50/60 Hz,
- Medrad Mark V Pro Vis is an injection system - syringe for the administration of contrast for angiographic studies,
- It is designed to be easy to use, from the legibility of the display and controls to the ergonomics and functionality of the injector and control panel,
- The programmed microprocessor helps protect against excessive volume, flow and pressure values,
- Constantly updated syringe volume,
- Control panel can be rotated 180°,
- Equipped with a mechanical stop that is automatically set and locked to physically limit injection to the selected volume,
- The set position is verified by LEDs located on the injector head,
- Up to four flow rates can be programmed,
- Easy integration with any imaging system,
- Control panel divided into sections for efficient syringe programming,
- Large, secure handles and maneuverable casters make the unit easy to maneuver,
- Clear and easy to read control panel is easy to clean with foiling,
- Specifications:
 - Charging speed: 5 - 10 mL/s,
 - Flow speed:
 - For 60 mL syringe:
 - 0.3 - 10 mL/s or mL/min or mL/h, step 0.1 mL,
 - 10 - 20 mL/s, step 1 mL,
 - 10 - 59 mL/min or mL/h, step 1 mL,
 - For 150 and 200 mL syringes:
 - 0.3 - 10 mL/s or mL/min or mL/h, step 0.1 mL,
 - 10 - 50 mL/s, step 1 mL,
 - 10 - 59 mL/min or mL/h, step 1 mL,
 - Volume: from 0.5 mL for 60 mL syringe or from 1 mL for 150 and 200 mL syringes up to the maximum volume of the selected syringe, step 0.1 mL,
 - Maximum programmable pressure limit: 7584 kPa for mL/s unit,
 - Scan delay: 0 - 99.9 s, step 0.1 s,
 - Injection time: 0 - 650 s,
 - Flow rate rise/fall time: 0 - 9.9 s, step 0.1 s,
 - Syringe heating: 37° C,
 - Syringes supported: 60, 150, 200 mL
- Keypad on control panel in French,
- Included:
 - Power cord,
 - Operator button,
- Dimensions: 48 x 61 x 150 cm,
- Weight: 63.5 KG
- Cat 02,
- It has a current inspection and is ready for operation,
- Issued Technical Passport (Service Report) valid for 12 months,
- Warranty:
 - 6-months for domestic market (Poland),
 - 3-months for the international market,
 - Possibility to extend the warranty up to 12-months for domestic and international market for a surcharge,
- Financing options (Poland only): Installments, Leasing, Loan,

If you have any questions, please do not hesitate to contact us!

In case you don't find the product you are interested in, please get in touch with us and we will do our best to find the perfect solution for YOU.

