

PRAISTON Sp. z o.o. ul. Górowska 32 64-100 Leszno Polska Biuro: +48 65 527 01 67 Serwis:+48 782 844 000 Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży Krzysztof Wybieralski +48 882 762 006

kw@praiston.pl



ULTHERA UC-1 Non-invasive facelift system (Reconditioned)

- · Reconditioned (used),
- Technical condition: very good,
- · Visual condition: very good,
- Real photos of the product,
- Made in the USA, (2019),
- Power supply: 230 V,
- Frequency: 50/60 Hz,
- The Ulthera system is indicated for use as a non-invasive dermatologic aesthetic treatment for:
 - · Brow lift,
 - · Elevating loose tissue in the chin (under the chin) and neck,
 - Reducing lines and wrinkles of the décolletage,
- Integrates ultrasound imaging capabilities with ultrasound therapy capabilities. The imaging function allows the operator to visualize the skin and subcutaneous areas of interest prior to treatment. It also allows the operator to ensure adequate skin contact to deliver energy to the desired depths. The therapy function directs acoustic waves to the treatment area. This acoustic energy heats the tissue through rubbing losses during energy absorption, creating discrete points of coagulation,
- The system consists of two basic components:
 - The control unit:
 - 15" TFT LCD monitor with 1024 x 768 resolution with integrated touch screen,
 - Graphical user interface.
 - Menu in English,
- Customizable display of operating conditions, including equipment activation status, treatment parameters, system messages and prompts, and ultrasound images,
 - Built-in:
 - 3 x USB 2.0 ports (two on the front panel, one on the rear panel),
 - · Emergency stop,
- Handpiece Ulthera transducer:
 - Allows ultrasonic visualization up to 8 mm deep below the skin surface to:
 - Ensure proper connection of the transducer to the skin,
 - Confirm the correct depth of treatment to avoid bone,
 - · Has two types of buttons: one for imaging (SEE) and one for therapy delivery (TREAT),
- · English language menu,
- Includes:
 - · User manual in English (PDF),
 - · Power cord,
 - 4 transducers included:
 - BS 4 13 (9891 of 10000 applications remaining),
 - DS 4 8.0 (9815 of 10000 applications remaining),
 - DS 4 4.5 (9910 of 10000 applications remaining),
 - BS 4 13 (8602 of 10000 applications remaining),
 - 3 mm adapter,
 - Safety glasses,
- Dimensions: 43 x 44 x 42 cm,
- Weight: 4 kg,
- It has a current inspection and is ready to work,
- Issued Technical Passport (Service Report) valid for a period of 12 months,
- Warranty:
 - · 6-months for domestic market (Poland),
 - 3-months for the international market,
 - · Possibility to extend the warranty up to 12-months for domestic and international market for a surcharge,
- Financing options (Poland only): Installments, Leasing, Loan,

If you have any questions, please do not hesitate to contact us!

In case you don't find the product you are interested in, please get in touch with us and we will do our best to find the perfect solution for YOU.



www.praiston.pl