

CONMED LINVATEC arthroscope set (D4000A, IM4000, LS8000) (Reconditioned)

Reconditioned (used),
Technical condition: very good,
Visual condition: very good,
Real photos of the product,
Manufactured by U.S.A.,
Power supply: 230 V,
Frequency: 50/60 Hz,
The set includes:
CONMED FS-P2603D monitor:
Manufacture U.S.A., (2015),
Power supply: 24 V,
Power: 70 W,
The FS-P2603D surgical monitor's excellent image quality and wide viewing angles offer the optimal visual requirements required in today's operating room,
FS-P2603D
has the latest advanced features, including precise image control and built-in DC output for smaller component needs. Images can be zoomed, pan left or right, or freeze frames. Two separate video signals can be displayed as picture-in-picture or side-by-side,
Technical specifications:
Display: 26" inch TFT LCD (IPS),
Resolution: 1920 x 1080 px,
Aspect ratio: 16:9,
Brightness: 450 cd/m
2
,
Contrast ratio: 1400:1,
Input signal:
2x DVI-D / 2x SD/HD/3G-SDI (BNC) / 2x SOG / 1x VGA (D-sub) / 1x C-Video (BNC) / 1x S-Video (DIN) / 1x Component (RGBS, YPbPr) (5 x BNC),
Output signal:
2x DVI-D / 2x SD/HD/3G-SDI (BNC) / 2x SOG / 1x C-Video (BNC) / 1x S-Video (DIN) / 1x Component (RGBS, YPbPr) (5 x BNC),
CONMED D4000A arthroscopy resection console:
U.S.A. manufacture,
Power: 230 V,
Power: 500 VA,
Easy-to-use interface,
Automatic fluid control with pump
CONMED 10K
,
Two "plug and play" ports provide continuous, uninterrupted power Versatility - supports 31 handpieces, 5 languages, built-in wireless features to support multiple wireless foot controllers and allows customizable user profiles,
D4000A has a standalone pump with irrigation or tip cooling for ENT applications,
CONMED IM4000 camera processor:
U.S.A. manufacture, (2013),
Power: 230 V,
Power: 80 VA,
Intuitive interface
OF THE IM4000 CAMERA PROCESSOR
simplifies its use in demanding clinical environments, allowing surgeons to focus fully on their patients. With simple adjustments to parameters such as brightness and contrast , users can quickly optimize the image according to the specific needs of each procedure, thereby increasing diagnostic and operational efficiency,
High-resolution camera
CONMED IM4000
represents the pinnacle of innovation in medical endoscopy. With advanced image processing, it provides unparalleled visual quality that enables surgeons to quickly and accurately identify bone and soft tissue features . The faithful reproduction of natural colors makes it a versatile tool, ideal for a variety of endoscopic procedures,
Technical specifications:
White balance - triggered automatically by a button on either the panel or the camera head,
White balance range: 2800K to 6500 K,
Automatic shutter speed: From 1/60 sec. to 1/10,000 sec,
CONMED IM4120 Camera:
U.S.A. manufacture, (2013),
Autoclavable camera head
CONMED IM4120 HD
is designed with an ergonomic design and enhanced digital imaging features to provide clear and accurate high-resolution images in the operating room,
It can withstand extreme autoclaving conditions, and the ShockFlex prism mount extends its life,
CONMED ERGO D4240 shaver handle:
U.S.A. manufacture,
Ergonomically designed handle provides optimal balance and control regardless of how the device is operated,
Device Specifications:
Ergonomic design,
Bi-directional blade input,
Up to 12,000 rpm for aggressive bone removal,
Thorn 5/31" handle mount,
CONMED LS8000 light source:
U.S.A. manufacture, (2016),
Power supply: 230 V,
Power: 129 VA,
Built-in communication from the IM8000 camera heads with the light source allows easy control of light output in standby mode. This avoids excessive heat in the range that can enter the curtain,
Energy-efficient LED technology uses less energy than Xenon-style bulbs and can last 40 times longer than other types of light sources,
Achieves consistent light output, creating a reliable color spectrum throughout its lifetime,
Technical specifications:
Lamp type: high-power white LED light,
Lamp color temperature: 5500 - 7500°K,
Lamp power: 90 W,
CONMED 10K irrigation pump:
U.S.A. manufacture, (2015),
Power supply: 230 V,
Power: 65 VA,
Technical specifications:
Maximum pressure: 150 mmHg,
Maximum flow rate: 2000 ml/min,
Maintains stretch even in the most demanding situations,
Intuitive one-hand cassette loading,
English language menu,
Instrumentation placed on CONMED WA54 mobile endoscopy cart placed on 4 casters (2 braking.),
Included:
Fiber optic cable
CONMED LG1050
,
Arthroscope cover
CONMED T5802
,
Conical obturator
CONMED QL6102
,
CONMED arthroscope 4 mm. - 30° - working length: 17 cm,
2 pcs. - double blades
CONMED 5.5
,
Double blades
CONMED 4.2
,
EASCULAP autoclavable container with accessories,
Dedicated autoclavable CONMED container for accessories,
Power cords,
Dimensions:
Monitor: 75 x 23 x 42 cm,
Overall: 60 x 62 x 190 cm,
Weight: 140 KG,
It has a current inspection and is ready for operation,
Issued Technical Passport (Service Report) valid for 12 months,
Warranty:
6-months for domestic market (Poland),
3-months for the international market,
Possibility to extend the warranty at a surcharge to 12-months for domestic and international markets,
The warranty period does not include bulbs and other light sources installed in the device,
Possibility of financing (Poland only): Installments, Leasing, Loan,

