



**PRAISTON Sp. z o.o.**  
ul. Górowska 32  
64-100 Leszno  
Polska

Biuro: +48 65 527 01 67  
Serwis: +48 782 844 000  
Fax: +48 65 527 01 67

E-mail: [biuro@praiston.pl](mailto:biuro@praiston.pl)

Koordinator ds. sprzedaży  
Krzysztof Wybieralski  
+48 882 762 006

[kw@praiston.pl](mailto:kw@praiston.pl)



**GE CARESCAPE B650 Patient Monitor/Cardiac Monitor (Reconditioned)**

Reconditioned (used),  
Technical condition: very good,  
Visual condition: very good,  
Real product photos,  
Finnish production,  
Power supply: 230 V,  
Backup power supply: via 1 built-in 11.1 V / 6.21 Ah batteries (can be replaced with a new one for an additional fee),  
Frequency: 50/60 Hz,  
CARESCAPE B650 was designed with more effective healthcare in mind. It helps manage patient flow by providing doctors with the right clinical information when and where they are needed. Its intuitive design makes it easy to train staff of all experience levels, and upgradeability protects your investment for the long term,  
Combines the best of Marquette® Electronics and Datex-Ohmeda® monitors on a single platform,  
Advanced measurement modules offer a wide range of clinical measurements,  
The CARESCAPE PDM patient data module provides consistent hemodynamic monitoring during intra-hospital transport and trend data transfer,  
Innovative algorithms and solutions, such as GE EK-Pro and GE DINAMAP® and the 12SL™ diagnostic ECG recording system with direct bidirectional connectivity to the MUSE® system, help make accurate diagnoses,  
Advanced respiratory gas modules provide full respiratory monitoring with gas exchange measurements,  
A variety of parameters help assess the adequacy of anesthesia in the operating room, and in the intensive care unit facilitate weaning decisions,  
Aware® Gateway connectivity allows for connectivity to medical data collection systems using standard HL7 protocol,  
“Pages and Profiles” feature can increase the versatility and efficiency of patient management by enabling the monitors to be configured to meet departmental standards and patient populations,  
User-selectable display modes allow for 8 to 14 waveforms with screen overlays and fields, allowing the screen to be customized to the needs of staff and patients,  
Auto View on Alarm (AVOA) feature enables automatic distribution of high-priority alarms within the department,  
Built-in USB ports enable connection of keyboards, mice, barcode scanners and other data entry devices,  
Trim Knob® and touchscreen or hardware buttons enable easy use of basic functions,  
Dedicated software and parameters for anesthesia, postoperative, intensive care and neonatal intensive care make it easy to configure the monitor to meet specific clinical needs,  
Ergonomically oriented compact design with rotating module frame allows it to fit into various clinical environments and can be modified with modules multi-parameter and other options,  
Display:  
Screen: 15” inches,  
Touchscreen color liquid crystal display with active matrix technology,  
Resolution: 1024 x 768 pixels (XGA),  
Number of records: 8 single, up to 14 with overlays and windows,  
Plotting speed: 0.625 / 6.25 / 12.5 / 25 / 50 mm/s,  
Configuration: Automatic configuration with available parameters. Manual configuration of up to 8 user-configurable profiles covering specific clinical configurations and up to 6 user-configurable screen pages for each profile,  
Controls: navigation knob, touch screen, hardware buttons,  
Device equipped with the following modules:  
EPSMP-00:  
SpO2 saturation measurement,  
NIBP pressure measurement,  
ECG measurement,  
Temperature measurement,  
2x invasive IPB pressure measurement,  
E-CAIOV-00:  
Measurements:  
O2,  
CO2,  
N2O,  
5 anesthetics,  
Possibility to select menu languages: PL, ENG, CHIN, CS, DAN, DUT, FIN, FR, GER, HUNG, IT, JP, NORD, PT, RUS, ESP, SWED,  
The device has visible traces that do not affect its comfort of use,  
Included:  
New SPO2 sensor,  
New ECG cable 3-lead,  
New NIBP cuff with air tube,  
New temperature sensor (not included - can be retrofitted for an additional fee),  
User manual in English (PDF),  
Power cord,  
Overall dimensions: 40 x 22 x 32 cm,  
Weight: 12 KG,  
Cat 04,  
It has a current inspection and is ready to work,  
Technical Passport (Service Report) issued valid for 12 months,  
Warranty:  
6 months for the domestic market (Poland),  
3 months for the international market,  
Possibility of extending the warranty for an additional fee to 12 months for the domestic and international market,  
Financing options (Poland only): Installments, Leasing, Loan,

