



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67
E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006
kw@praiston.pl



EPENDORF CENTRIFUGE 5702 R laboratory centrifuge (Ex-Display)

New (exhibition),
Real product photos,
German production,
Power supply: 230 V,
Frequency: 50/60 Hz,
Power: 380 W,
Centrifuge 5702 R is a model of a centrifuge with cooling for heat-sensitive samples,
Built-in backlit LCD display,
Product features:
Compact design, thanks to which the device fits on any laboratory table,
Very quiet operation,
Low height of the device allows easy insertion and removal of samples,
SOFT braking function for slow start and braking,
Optimized for cell separation by centrifugation in a gradient,
The "At set RPM" function starts the clock after reaching the selected rotational speed; to ensure repeatable spinning,
Key lock prevents accidental parameter changes,
Stainless steel rotor chamber is easy to clean,
Electronic imbalance detection for maximum safety,
Automatic lid lock,
Time adjustment: 0.5 - 99 min. and continuous centrifugation,
Special solutions for Centrifuge 5702 R:
Temperature range: from -9 °C to 40 °C,
FastTemp function for fast cooling,
Constant cooling ensures that the temperature is maintained at a constant level after the work is finished - samples are constantly cooled,
ECO function that switches the device off after 8 hours of inactivity, allowing to reduce energy consumption and extend the compressor's life,
Two program buttons allowing to save routine programs,
Technical specifications:
Max RCF: 3,000 × g,
Max speed: 4400 rpm,
Max capacity: 4 x 100 ml,
Noise level:
Keyboard in the control panel in English,
Included:
Swing-out rotor A-4-38,
4 pcs. - test tube cup,
4 pcs. - adapter 4 x 10 ml.,
4 pcs. - adapter 4 x 7 ml.,
Instruction manual in Polish (PDF),
Power cord
Dimensions: 38 x 58 x 26/60 cm (with open cover),
Weight: 36 KG,
Cat 02,
It has a current inspection and is ready to work,
Issued Technical Passport (Service Report) valid for 12 months,
Warranty:
6 months for the domestic market (Poland),
3 months for the international market,
Possibility of extending the warranty for an additional fee to 12 months for the domestic and international market,
Financing options (Poland only): Installments, Leasing, Loan,

