

PRAISTON Sp. z o.o. ul. Górowska 32 64-100 Leszno Polska Biuro: +48 65 527 01 67 Serwis:+48 782 844 000 Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży Krzysztof Wybieralski +48 882 762 006

kw@praiston.pl



Germicidal lamp NBVE 60/30 PL (Reconditioned)

Reconditioned (used),

Technical condition: very good, Visual condition: very good, Real photographs of the product,

Polish manufacture,

Bactericidal and virucidal flow-through NBVE 60/30 PL lamp with two timers,

The use of energy-saving bactericidal and virucidal flow-through NBVE series lamps is one of the most effective methods of disinfection, This device can be used in two ways: when patients and staff are indoors (in which case the airflow function of the lamp is used and thus the biocidal UV-C radiation does not escape to the outside) or when no one is in the room,

In this case, external emitters are activated, which emit radiation with a wavelength of 253 nm into the environment and thus effectively inactivate moulds, bacteria, viruses, fungi and any other microorganisms from the irradiated surfaces,

Designed for use:

Hospitals (operating theatres, treatment rooms, dressing rooms, sick rooms, recovery rooms, isolation rooms, dirty rooms,

Clinics (doctor's offices and treatment rooms),

Laboratories,

Pharmacies,

Pharmaceutical industry, food-processing industry, cosmetics industry,

Hotel and catering industry,

Advantages of NBVE 60/30 PL germicidal lamp:

The device has all the required certificates,

The lamp has passed tests in a microbiological laboratory,

Type of casing: made of acid-resistant sheet metal - thanks to this it disinfects the air more effectively, and keeping the device clean does not cause any problem,

Energy-saving model: it significantly reduces electricity consumption,

Guarantee of a high degree of air disinfection,

Purpose: the device is ideal for use in operating theatres, patient rooms, corridors, emergency rooms, nurseries, kindergartens and production halls.

The device has two radiant heaters: the external one allows the entire room to be disinfected when the room/office users are not present; the internal one allows effective disinfection of viruses, fungi, moulds and other microorganisms even when the office is in operation (i.e. when the staff and patients are in the room), when staff and patients are in the room),

The forced air flow through the UV-C chamber ensures that the harmful radiation emitted by the internal radiators does not escape,

Technical data:

The lamp is placed on a mobile stand,

Supply voltage: 230 V 50 Hz, Power consumption: 115 W,

Internal UV-C emitting element: 2 x 30W, External UV-C emitting element: 1 x 30W, UV-C irradiance at 1 m: $100 \mu W/cm^2$,

Radiant life: 9000 h, Fan capacity: 132 m3/h, Disinfected volume: 25 - 50 m3, Lamp operating range: 10 - 20 m2, Protection class ppor: I,

Housing type: IP 20, Dimensions: Base width: 60 cm, Height: 175 cm,

It has an up-to-date inspection and is ready for operation, Issued Technical Passport (Service Report) valid for 12 months,

Warranty:

6 months for the domestic market (Poland),

3 months for the international market,

Possibility to extend the warranty to 12 months for the domestic and international market for a surcharge,

Possibility of financing (Poland only): Instalments, Leasing, Loan,



www.praiston.pl