



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67
E-mail: biuro@praiston.pl

Koordinator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006
kw@praiston.pl



EPENDORF CENTRIFUGE 5415C Laboratory Centrifuge (Reconditioned)

Reconditioned (used),
Technical condition: very good,
Visual condition: very good,
Real photos of the product,
German production,
Power supply: 230 V,
Frequency: 50/60 Hz,
Power: 250 W,
Eppendorf 5415C
is a compact, low-noise centrifuge that reaches a maximum speed of 14,000 rpm and an RCF of 16,000 x g in ten seconds. The total centrifugation time is controlled by a built-in 30-minute timer that automatically shuts down the unit,
The 5415C centrifuge
has microprocessor control of operating functions that allows it to operate at very short spin times. The LED indicator light turns on and off at 1-second intervals for counting,
The Eppendorf
also has a safety switch that prevents the centrifuge from starting when the lid is open, and a safety lock that prevents the lid from opening while the centrifuge is running. The 5415C's covered, quick-release, fixed-angle rotor provides better aerosol control and accommodates up to eighteen 1.5-2.0 ml tubes. The centrifuge stops within 12 seconds,
Specifications:
Speed infinitely adjustable from: 1,000 to 14,000 rpm,
Maximum speed: 14,000 rpm,
Maximum RCF: 16,000 x g,
Timer: 30 min,
Acceleration time: approx. 10 sec,
Deceleration time: approx. 12 seconds,
Rotor:
F-45-18-11 18-place rotor for 1.5 / 2.0 ml tubes,
Bore diameter: 11 mm,
Bore angle: 45°,
Max. load per bore: 4.2 g,
Max. rotational speed: 14,000 rpm,
Max. centrifugal force: RCF = 16,000,
K-value for rotor: k = 469 h,
Max. permissible liquid density: 1.2 g-ml-1,
Accurate control of speed, acceleration and deceleration by microprocessor,
30 min timer and momentary button for short spins,
Safety cover prevents operation when the centrifuge is open,
Includes:
Rotor F-45-18-11,
Power cord,
Dimensions: 29 x 21 x 28 cm,
Weight: 8 KG,
Has a current inspection and is ready for operation,
Issued Technical Passport (Service Report) valid for 12 months,
Warranty:
6-months for domestic market (Poland),
3-months for the international market,
Possibility to extend the warranty up to 12-months for domestic and international market for a surcharge,
Financing options (Poland only): Installments, Leasing, Loan,

