



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67
E-mail: biuro@praiston.pl

Koordinator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006
kw@praiston.pl



ZOLL R SERIES PLUS defibrillator (Reconditioned)

Reconditioned (used),
Technical condition: very good,
Visual condition: very good,
Real photos of the product,
Manufactured by U.S.A.,
Power supply: 230 V,
Emergency power supply: through 1 new built-in batteries 10.8 V / 5.8 Ah -
(not included) can be retrofitted at additional cost,
Frequency: 50/60 Hz,
Menu in language: English,
R Series defibrillator
is widely used in hospitals, especially in cardiology and intensive care units,
Using ZOLL's advanced technology, it provides high efficiency electrotherapy (defibrillation, cardioversion, pacing) and enables real-time monitoring of CPR quality,
Provides audible and visual feedback to assist the rescuer in continuously conducting high-quality CPR,
Visual Perfusion Index (PPI) provides information on the compliance of the combination of compression rate and depth with guideline recommendations,
Features:
Real CPR Help for ALS
- Provides real-time feedback on depth and rate of compressions,
OneStep system
- Simplifies defibrillation, pacing and monitoring with one set of electrodes,
Code-Readiness Testing System
- ensures that the device is always ready for emergency use,
Two-phase rectilinear defibrillation technology
- provides more effective defibrillation with less energy consumption,
Advisory defibrillation
- complies with AHA/ERC guidelines for shock delivery ,
Built-in test port
- enables seamless system inspection and maintenance,
Compact Flash card slot
- enables data storage and easy transfer of critical event logs,
Technical specifications:
Liquid crystal LCD display: 6.5" inch,
Power selection:
Adult: 1 / 2 / 3 / 4 / 5 / 6 / 7 / 8 / 9 / 10 / 15 / 20 / 30 / 50 / 75 / 100 / 120 / 150 / 200 J,
Child: 1 / 2 / 3 / 4 / 5 / 6 / 7 / 8 / 9 / 10 / 15 / 20 / 30 / 50 / 70 / 85 / 100 / 120 / 150 / 200 J
(OneStep pediatric electrodes only)
,
CPR monitoring:
Compression depth: 1.9 cm to 7.6 cm (+/- 0.6 cm),
From 50 to 150 compressions per minute,
Heart rate measurement range: from 30 to 300 BPM,
Built-in audible and visual alarm system,
Built-in printer with paper width: 9 cm (print speed 25 mm/sec.),
Includes:
User manual in English (PDF),
Power cord,
ECG 3-lead cable,
SPO2 cable,
ZOLL EtCO2 Sensor,
APEX set of hard spoons,
Dimensions: 35 x 34 x 28 cm,
Total weight: 7 KG,
Cat D144,
Has up-to-date inspection and is ready for operation,
Issued Technical Passport (Service Report) valid for 12 months,
Warranty:
6-months for domestic market (Poland),
3-months for the international market,
Possibility to extend the warranty up to 12-months for domestic and international market for a surcharge,
Financing options (Poland only): Installments, Leasing, Loan,

