



**PRAISTON Sp. z o.o.**  
ul. Górowska 32  
64-100 Leszno  
Polska

Biuro: +48 65 527 01 67  
Serwis: +48 782 844 000  
Fax: +48 65 527 01 67

E-mail: [biuro@praiston.pl](mailto:biuro@praiston.pl)

Koordynator ds. sprzedaży  
Krzysztof Wybieralski  
+48 882 762 006

[kw@praiston.pl](mailto:kw@praiston.pl)



**Anesthesia apparatus DRAGER FABIUS GS (Respirator-Ventilator) (Reconditioned)**

Product temporarily unavailable

Reconditioned (used),

Technical condition: very good,

Visual condition: very good,

Real photos of the product,

German production,

Power supply: 230 V,

Emergency power supply: via 2 new built-in 12 V / 3.2 Ah batteries,

Frequency: 50/60 Hz,

Software: 3.37b,

Has two ports for vaporizers with common Dräger DW-2000 connector systems ,no vaporizers included - can be retrofitted at additional cost,

Respirator driven by an electric motor (electronically controlled),

Supplied with gases: 2 x O

2

, 2 x N

2

O, AIR,

Can be supplied with gases from cylinders: O

2

, N

2

O,

Ventilator measurement functions:

PMAX (V): 15 - 70 mbar,

VT: 20 - 1400 ml,

f: 4 - 60 bpm,

Ti/Te: 4:1 to 1:4,

Tip/Ti: 0% - 50% ,

PEEP: 0 - 20 mbar,

Pinsp (P): 5 - 60 mbar,

Insp Flow: 10 - 75 L/min,

Infinitely adjustable gas flow: O2, AIR, N2O, from 0.0 to 12 L/min, (digital displays + pressure gauges),

Compact patient breathing system located on a mobile arm,

Replaceable soda lime tank,

Built-in LED monitor with gas measurement function: O2, AIR, N2O, and control panel and ventilator function display,

Easy to use and easy to read display,

Equipped with:

60 x 30 cm work surface,

3 drawers, 43.5 x 30 x 17.5 cm, top lockable,

Slats for attaching additional accessories,

2 holders for gas cylinders,

Mobile, on casters, including 2 with brake,

Selectable menu in the following languages: PL SK, CS, HR, HU, BG, RU, EN, FR, DE, ES,

Includes:

DRAGER INFINITY DELTA cardiac monitor / patient monitor:

Reconditioned (used),

Technical condition: very good,

Visual condition: very good,

Real photos of the product,

Manufactured by U.S.A., (2006),

Power supply: 230 V,

Frequency: 50/60 Hz,

Specifications:

10.4" liquid crystal TFT-LCD color display,

Resolution: 640 x 480 px,

Foiled control panel,

Navigation dial makes it easy to enter information and navigate the screen,

Convenient hanging handle and durable case for easy portability,

Audible and visual alarms,

Equipment:

ECG - 3-lead cable,

SOP

2

- SOP sensor

2

,

NIBP - New cuff with air line,

TEMP - No sensor

(can be retrofitted at additional cost),

MultiMed collection cable,

Power cord,

DRAGER connection docking station:

Provides monitor mounting on the bench, power supply, connection of additional screen and recorder, and data transfer,

DRAGER SCIO FOUR OXI PLUS Gas Module:

The monitor samples patients' breath gases,

Dräger Scio gas modules provide precise measurements of inspiratory and expiratory concentrations of O2, CO2 , enflurane, halothane, isoflurane, sevoflurane, desflurane and N2O,

The measurement results are transmitted to the Dräger Infinity monitor and displayed in real time and as trends,

The module features automatic agent identification and integrated oxygen concentration measurement,

Equipped with WaterLock 2 water trap, providing greater protection against infection,

Includes:

DRAGER FABIUS GS user manual in English (PDF),

DRAGER INFINITY DELTA patient monitor user manual in Polish (PDF),

Power cord,

Gas supply hoses with customer-selectable tips (AGA or DIN),

Patient breathing system,

Sampling line for measuring gases,

SPO sensor

2

clip-on,

Cuff with air line,

ECG 3-lead cable,

MultiMed collection cable,

Dimensions:

Apparatus: 89 x 77 x 160 cm,

Cardiomonitor: 36.5 x 24 x 17 cm,

Weight:

Apparatus: 117 kg,

Cardiomonitor: 6 kg,

Cat 04,

The price of the apparatus includes delivery, equipment installation and training,

In the domestic market (Poland), in the case of installation of the device within 30 days from the date of delivery of the equipment, installation and training are free, after exceeding this period, these services will be charged,

Has a current inspection and is ready for operation,

Has a current inspection and is ready for operation,

Issued Technical Passport (Service Report) valid for a period of 12 months,

Warranty:

6-months for domestic market (Poland),

3-months for the international market,

Possibility to extend the warranty up to 12-months for domestic and international market for a surcharge,

Financing options (Poland only): Installments, Leasing, Loan,

