



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67
E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży
Krzysztof Wybierski
+48 882 762 006
kw@praiston.pl



BTL-08 MT PLUS ECG apparatus (Reconditioned)

Reconditioned (used),

Technical condition: very good,

Visual condition: very good,

Real photos of the product,

U.K. production,

Power supply: 230 V,

Emergency power supply: through a new built-in 12 V / 1.3 Ah battery,

Frequency: 50/60 Hz,

Features:

12-lead ECG for printing and recording from 12 leads with color touch screen,

5.7" touch screen with 3, 4, 6 or 12 leads,

Screen resolution: 320x240,

Alphanumeric keyboard, function keypad and touch screen buttons,

Contact control of each electrode,

Paper width: 112mm,

Paper type: roll,

Paper type: thermal/external laser or inkjet printer, fax, folding,

Direct printing from a regular printer (via USB port, independent of PC, printing on A4 office paper),

Sensitivity: 2.5 / 5 / 10 / 20mm/mV,

Print speed: 5 / 10 / 25 / 50mm/sec,

Network interference filter: 50-60Hz,

Muscle interference filter: 25, 35Hz,

Isoline filter: 0.05 (3.2s) / 0.11 (1.5s) / 0.25 (0.6s) / 0.50 (0.3s) / 1.50 (0.1s) / splines,

Automatic filters: autoadaptive,

Number of printed discharges: 3 / 4 / 6 / 12 / 3x4+1 / 3x4+2 / 3x4+3 / 4x3+1 / 6x2+1 / 6x2+2,

Up to 120 examinations in camera memory (10 sec.),

Unlimited number of profiles,

Manual or automatic mode,

Long ECG recording,

Real-time recording and synchronization in automatic mode,

Backward ECG recording,

Defibrillation protection,

Cardiac pacemaker detection,

Technical specifications:

Digital resolution: 3.9 UV,

Analog-to-digital processing A/D 13 bits,

Sampling frequency 2kHz/12 leads, 18 kHz/1 lead,

Dynamic range 15.9mV,

Voltage polarization ± 400 mV,

Max. Voltage compliance ± 5 V,

Input impedance more 20MOhm,

Attenuation of concurrent signal more 100dB,

Safety standards IEC 601-1 / IEC 601-2-25 / IEC 601-1-2 / IEC 601-1-4 / ISO 14971,

Selectable language menu: EN, CS, GER, PL, ESP, FR, IT, PT, RU, RU, TR, KR, NO, SE, HUN, KZ,

Keypad on control panel in language: English,

Device placed on a mobile dedicated cart,

Includes:

User manual in English (PDF),

Power cord,

10-lead ECG cable,

Overall dimensions: 50 x 50 x 154 cm,

Weight: 25 KG,

Has a current inspection and is ready for use,

Issued Technical Passport (Service Report) valid for 12 months,

Warranty:

6-months for domestic market (Poland),

3-months for the international market,

Possibility to extend the warranty up to 12-months for domestic and international market for a surcharge,

Financing options (Poland only): Installments, Leasing, Loan,



Barcode
PRAISTON



Barcode
PRAISTON



Barcode
PRAISTON



Barcode
PRAISTON



Barcode
PRAISTON



Barcode
PRAISTON

