



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67
E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży
Krzysztof Wybierski
+48 882 762 006
kw@praiston.pl



CU Medical iPAD SP1 defibrillator (New)

New,

South Korean manufacture,

The iPad SP1's simple design, intuitive operation aided by light and voice messages, and high-quality materials used in the production of the iPad SP1 make it a reliable device that will be great for use in public places as well as in workplaces,

With easy-to-read backlit illustrations that highlight key commands, the AED intelligently guides the user through the entire assistance process. The gentle, reassuring tone of the voice messages, the volume of which is automatically adjusted to the noise level, makes the rescuer's effectiveness much higher than with other AEDs,

Defibrillators of the iPad series are characterized by high resistance to water, dust and mechanical damage, so they are an ideal choice wherever there are difficult working conditions. AED iPAD will successfully meet the expectations of qualified rescue units and uniformed services, LCD screen allows you to quickly check the status of batteries and electrodes,

Very well solved pediatric mode in the form of sliding switch, eliminates accidental activation of the "child" mode,

CU Medical iPAD SP1 is a semi-automatic external defibrillator,

Features and advantages of the defibrillator:

Semi-automatic operation - the defibrillation shock is triggered by pressing a button, when the shock button flashes then the device is ready to release the electrical impulse,

Universal electrodes: for defibrillation of adults and children,

Pediatric mode: change the operation of the device to pediatric mode at the flip of a switch,

Adaptive message volume: in case of noise, the defibrillator automatically adjusts the volume of voice messages,

Message language: Polish,

Self-tests: a choice of daily, weekly or monthly self-tests, through which the device's technical condition, battery capacity and electrode life are regularly checked,

Data recording: thanks to the memory card, the defibrillator has the ability to record patient parameters or full recording of 5 rescue actions (maximum duration is 3 hours),

Durable battery: provides a 5-year standby period or allows up to 200 discharges,

IP55: resistant to water, dust and mechanical damage,

Defibrillation parameters:

Output energy: for adult patients is 150 J at 50 Ω , for pediatric patients is 50 J at 50 Ω ,

Shock charging time: about 6 seconds,

Charging time after CPR: about 6 seconds,

The waveform is a two-phase e-cube that is truncated exponentially,

ECG:

Level-II ECG lead,

Frequency response from 1 Hz to 30 Hz,

Patient impedance range of 25 Ω to 175 Ω ,

Meets ANSI/AAMI DF80 requirements,

Operational notes:

Buttons: power button (on/off); discharge button; 'i' (information) button; sliding defibrillation mode switch (adult/child),

LCD display: displays device status, battery level and electrode status,

Speaker: gives voice commands. The device analyzes the level of ambient noise and automatically adjusts the volume of the commands to make them clearly audible,

Tests:

Automatic: self-diagnostic test for on/off, run time. Daily, weekly and monthly tests,

Manually: test regarding the installation of the battery (performed when the user inserts the battery in the appropriate place in the device),

Battery:

Power: 12V, 4.2Ah LiMnO₂, Longlife,

Lasts for 200 discharges or 8 hours of continuous operation,

5 year warranty,

Temperature range: in operation mode from 0 °C to 43 °C, in storage mode: from -20 °C to 60 °C,

Electrodes:

CUA1007S universal electrodes (adult/child): Electrode area: 85 cm², total cable length: 120 cm (inside package: 95 cm, outside: 25 cm), shelf life: up to 36 months,

CUA1102S electrodes for children (optional for purchase): Electrode area: 85 cm², total cable length: 120 cm (inside package: 80 cm, outside: 40 cm), shelf life: up to 30 months,

Data storage and transfer:

Internal memory: 5 separate operations lasting up to 3 hours each,

SD card: External memory, data can be copied from internal memory to SD card,

IrDA: for communication with a computer,

Norms (standards):

Sealing: IEC 60529: IP55,

ESD: Meets IEC 61000-4-2:2008,

EMI emission: Meets IEC 60601-1-2 standard,

EMI immunity: Meets IEC 60601-1-2 standard,

Vibration: Meets military standard - in operation: MIL-STD-810G Fig. 514.6E-1, in standby mode: MIL-STD-810G Fig. 514.6E-2,

Altitude: 0 to 4.572 km (in operation and standby mode),

Resistant to dropping from a height of 1.2 m on any surface,

Environmental conditions: operating temperature: 0 to 50°C, storage temperature: 0 to 50°C, transportation temperature: -20 to 60°C,

Weight and dimensions:

Dimensions (W x L x H): 26 x 25.6 x 6.95 cm,

Weight: 2.4 kg including battery and electrodes,

The kit includes:

iPAD SP1 AED Defibrillator,

5-year battery,

Universal electrodes,

Carrying bag,

Mini-fridge,

Operating Instructions,

Has a current Technical Passport issued,

Warranty: 5 years,

Financing options (Poland only): Installments, Leasing, Loan,



PRASTON



PRASTON



PRASTON



PRASTON



PRASTON



PRASTON



PRASTON



PRASTON