



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordinator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



BTL-08 MT PLUS ECG apparatus (Reconditioned)

Reconditioned (used),
Technical condition: very good,
Visual condition: very good,
Real photos of the product,
U.K. production,
Power supply: 230 V,
Emergency power supply: through a new built-in 12 V / 1.3 Ah battery,
Frequency: 50/60 Hz,
Features:
12-lead ECG for printing and recording from 12 leads with color touch screen,
5.7" touch screen with 3, 4, 6 or 12 leads,
Screen resolution: 320x240,
Alphanumeric keyboard, function keypad and touch screen buttons,
Contact control of each electrode,
Paper width: 112mm,
Paper type: roll,
Paper type: thermal/external laser or inkjet printer, fax, folding,
Direct printing from a regular printer (via USB port, independent of PC, printing on A4 office paper),
Sensitivity: 2.5 / 5 / 10 / 20mm/mV,
Print speed: 5 / 10 / 25 / 50mm/sec,
Network interference filter: 50-60Hz,
Muscle interference filter: 25, 35Hz,
Isoline filter: 0.05 (3.2s) / 0.11 (1.5s) / 0.25 (0.6s) / 0.50 (0.3s) / 1.50 (0.1s) / splines,
Automatic filters: autoadaptive,
Number of printed discharges: 3 / 4 / 6 / 12 / 3x4+1 / 3x4+2 / 3x4+3 / 4x3+1 / 6x2+1 / 6x2+2,
Up to 120 examinations in camera memory (10 sec.),
Unlimited number of profiles,
Manual or automatic mode,
Long ECG recording,
Real-time recording and synchronization in automatic mode,
Backward ECG recording,
Defibrillation protection,
Cardiac pacemaker detection,
Technical specifications:
Digital resolution: 3.9 Uv,
Analog-to-digital processing A/D 13 bits,
Sampling frequency 2kHz/12 leads, 18 kHz/1 lead,
Dynamic range 15.9mV,
Voltage polarization $\pm 400\text{mV}$,
Max. Voltage compliance $\pm 5\text{V}$,
Input impedance more 20M Ω ,
Attenuation of concurrent signal more 100dB,
Safety standards IEC 601-1 / IEC 601-2-25 / IEC 601-1-2 / IEC 601-1-4 / ISO 14971,
Selectable language menu: EN, CS, GER, PL, ESP, FR, IT, PT, RU, TR, KR, NO, SE, HUN, KZ,
Keypad on control panel in language: English,
Device placed on a mobile dedicated cart,
Includes:
User manual in English (PDF),
Power cord,
10-lead ECG cable,
Overall dimensions: 50 x 50 x 154 cm,
Weight: 25 KG,
Has a current inspection and is ready for use,
Issued Technical Passport (Service Report) valid for 12 months,
Warranty:
6-months for domestic market (Poland),
3-months for the international market,
Possibility to extend the warranty up to 12-months for domestic and international market for a surcharge,
Financing options (Poland only): Installments, Leasing, Loan,

