



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



NGP 31 m Z negatoscope (New)

- A brand new product,
- Made in Poland,
- The NGP series of negatoscopes, including blinded ones designed for mammography, are modern products ideally suited for enhancing cancer diagnosis and improving the quality of performing examinations at the time of initial diagnosis,
- The product, thanks to its ability to narrow the area of the viewed image, will be helpful in daily work,
- **Advantages of using the NGP 31 m Z negatoscope:**
 - The model is equipped with four blinds, making it possible to view X-rays without side glare,
 - The ability to accurately "blend" the screen (including the edges) is especially important for small areas,
 - Light intensity: 6800 cd/m² ± 10%,
 - Negatoscope has the required certificates,
 - Case: powder coated, which determines its durability,
 - With the picture holder, negatives can be placed around the edge of the screen,
 - This type of negatoscope is available in high frequency version,
 - Instant ignition of fluorescent lamps,
 - Type of light emitted: day light 6500K,
 - By using this device, you can reduce energy consumption by up to 25%,
 - Protection for radiologist's eyes is provided by operation completely free of stroboscopic flicker effect,
 - Smooth regulation of light intensity in the range of 10-100% of the maximum value allows to optimally adjust the brightness of the screen to the described images and general lighting,
 - The combination of very good light, light intensity regulation and the use of blinds lead to better and more accurate description of details such as micro calcifications, which is especially important for mammographic description,
 - Very high uniformity of screen illumination,
- **Technical data:**
 - Supply voltage: 230 V 50 Hz,
 - Power consumption: 380 VA,
 - Screen luminance: 6800 cd/m² ± 10%,
 - Luminance regulation: Yes,
 - Regulation range: 10-100%,
 - Screen dimensions: 2 fields 96 x 30 cm,
 - Number of frames: 1,
 - Protection class: I,
 - Dimensions: 1240 x 940 x 120 mm,
 - Weight: 57 kg,
- Provided with an up-to-date Technical Passport,
- Guarantee: 12 months,

