



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



NBV 30 N LW germicidal lamp (New)

- A brand new product,
- Made in Poland,
- NBV 30 NLW direct-acting germicidal lamp with 4-field display timer,
- It is equipped with a digital counter with a microprocessor having a 4-field LED display, with an acoustic indication when the lamp is replaced,
- Irreversibly deactivates bacteria, viruses, molds, fungi and all other microorganisms,
- In addition, it has a high-quality reflector made of reflective aluminum,
- Turning the lamp on for just 20 minutes brings a rapid air disinfection effect between treatments.
- **The use of the device:**
 - Medical institutions,
 - Hospitals,
 - Pharmaceutical industry,
 - Food industry,
 - Cosmetics industry,
- **Advantages of NBV 30 N LW germicidal lamp:**
 - Counter type: LW - digital counter with a microprocessor with 4-field LED display, with acoustic indication of the moment of replacement of the radiator. Can be independently connected to previously purchased direct-acting and flow lamps,
 - Mounting method: W - wall-mounted,
 - The result of using this device is to increase the level of microbiological purity of the premises,
 - Emitted radiation: UV-C with a wavelength of 253.7 nm,
 - Irreversibly deactivate bacteria, viruses, molds, fungi and all other microorganisms,
 - The air and surface in the room where this lamp has been used are effectively disinfected,
 - High-quality reflector (material: reflective aluminum),
 - Purpose: the use in operating rooms (and other hospital rooms), in treatment rooms, as well as in the food, pharmaceutical and cosmetic industries,
 - The effectiveness of this device is confirmed by tests and numerous certificates,
- **Technical data:**
 - Wall mounted lamp,
 - Supply voltage: 230 V 50 Hz,
 - Power consumption: 33 W,
 - UV-C emitting element: 1 x 30 W,
 - UV-C irradiance at 1 m distance: 2.3 W / m²,
 - Radiant life: 9000 h,
 - Disinfectable area: 12 - 15 m²,
 - Lamp rotation (exposure angle can be adjusted): 200°,
 - Anti-schock safety class: I,
 - Case type: IP 20,
 - Operation type: continuous,
 - Chamber's dimensions: 960 x 85 x 135 mm,
 - Chamber's weight: 3 kg,
 - The extension's length: 120 mm,
 - Counter type: with 4-field display,
- It has a valid Technical Passport,
- Guarantee: 12 months,

