

PRAISTON Sp. z o.o. ul. Górowska 32 64-100 Leszno Polska Biuro: +48 65 527 01 67 Serwis:+48 782 844 000 Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży Krzysztof Wybieralski +48 882 762 006

kw@praiston.pl



NBV 30 S LW germicidal lamp (New)

- · A brand new product,
- · Made in Poland,
- NBV 30 SLW direct-acting germicidal lamp with 4-field display timer,
- It is equipped with a digital counter with a microprocessor having a 4-field LED display, with an acoustic indication when the lamp is replaced,
- Irreversibly deactivates bacteria, viruses, molds, fungi and all other microorganisms,
- In addition, it has a high-quality reflector made of reflective aluminum,
- Turning the lamp on for just 20 minutes brings a rapid air disinfection effect between treatments.

The use of the device:

- Medical institutions,
- Hospitals,
- · Pharmaceutical industry,
- Food industry,
- · Cosmetics industry.

Advantages of NBV 30 S LW germicidal lamp:

- Counter type: LW digital counter with a microprocessor with a 4-field LED display. With the use of sound, this model signals the need to replace the radiator. Our customers appreciate very much the possibility to connect this counter to previously purchased direct-acting lamps and flow devices,
 - · Mounting method: C ceiling
 - The result of using this device is to increase the level of microbiological purity of the premises,
 - This device emits UV-C radiation with a wavelength of 253.7 nm,
 - The action of this lamp irreversibly inactivates all bacteria, viruses, molds, fungi and other types of microorganisms,
 - Purpose: disinfection of the air and surfaces of a room,
 - High-quality reflector (material: reflective aluminum)
- Purpose: the use in operating rooms (and other hospital rooms), in treatment rooms, as well as in the food, pharmaceutical and cosmetic industries
 - The effectiveness of this device is confirmed by tests and numerous certificates,
 - The lamp has all required certificates,

Technical data:

- Ceiling mounted lamp,
- Supply voltage: 230 V 50 Hz,
- Power consumption: 33W,
- UV-C emitting element: 1 x 30W,
- UV-C irradiance at 1 m distance: 2.3 W / m2,
- Radiant life: 9000 h,
- Disinfectable area: 12 15 m2,
- · Lamp rotation (exposure angle can be adjusted): 230°,
- · Anti-schock safety class: I,
- Case type: IP 20,
- Operation type: continuous,
- Chamber's dimensions: 960 x 85 x 135 mm,
- Chamber's weight: 3 kg,
- The extension's length: 500 mm,
- · Counter type: with 4-field display,
- It has a valid Technical Passport,
- · Guarantee: 12 months,







