



PRAISTON Sp. z o.o.
ul. Górowska 32
64-100 Leszno
Polska

Biuro: +48 65 527 01 67
Serwis: +48 782 844 000
Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordinator ds. sprzedaży
Krzysztof Wybieralski
+48 882 762 006

kw@praiston.pl



NBV 2x30 N LW germicidal lamp (New)

- A brand new product,
- Made in Poland,
- NBV 2x30 NLW direct-acting germicidal lamp with 4-field display timer,
- The lamp is equipped with a digital counter with a microprocessor, which has a 4-field LED display, with an acoustic indication of the moment of replacing the radiator,
- This device emits radiation: UV-C with a wavelength of 253.7 nm,
- **The use of the device:**
 - Medical institutions,
 - Hospitals,
 - Pharmaceutical industry,
 - Food industry,
 - Cosmetics industry,
- **Advantages of NBV 30 N LW germicidal lamp:**
 - The effectiveness of this lamp is confirmed by numerous tests and all required certificates,
 - Counter: LW-digital counter with a microprocessor, which is equipped with a 4-field LED display. The functionality of this model is also enhanced by the possibility to independently connect it to previously purchased direct-action and flow lamps,
 - Lamp mounting method: W - wall-mounted,
 - The main task of the product is to raise and maintain the level of microbiological purity in the room,
 - This device emits radiation: UV-C with a wavelength of 253.7 nm,
 - Direct-acting germicidal lamp irreversibly deactivates bacteria, viruses, molds, fungi and all other microorganisms,
 - The effect of using this device: disinfection of air and surfaces,
 - Lamp reflector: made of high-quality reflective aluminum,
 - Purpose: for operating rooms, medical and treatment rooms, as well as food, pharmaceutical and cosmetic industry rooms,
- **Technical data:**
 - Wall mounted lamp,
 - Supply voltage: 230 V 50 Hz,
 - Power consumption: 66 W,
 - UV-C emitting element: 2 x 30 W,
 - UV-C irradiance at 1 m distance : 3.6 W / m²,
 - Radiant life: 9000 h,
 - Disinfectable area: 18 - 22 m²,
 - Lamp rotation (exposure angle can be adjusted): 200°,
 - Anti-schock safety class: I,
 - Case type: IP 20,
 - Operation type: continuous,
 - Chamber's dimensions: 960 x 85 x 145 mm,
 - Chamber's weight: 5 kg,
 - The extension's length: 120 mm,
 - Counter type: with 4-field display,
- It has a valid Technical Passport,
- Guarantee: 12 months,

