

PRAISTON Sp. z o.o. ul. Górowska 32 64-100 Leszno Polska Biuro: +48 65 527 01 67 Serwis:+48 782 844 000 Fax: +48 65 527 01 67

E-mail: biuro@praiston.pl

Koordynator ds. sprzedaży Krzysztof Wybieralski +48 882 762 006

kw@praiston.pl



NEOVO X 15 E Medical monitor (New)

- New.
- The X-15E is a rugged 15" display, perfect for environments where space is important. In high-traffic public areas, NeoV™ Glass optical glass protects the display from accidental damage. The attractive metal casing provides strength and durability for secure mounting anywhere. With built-in video support and multiple input options, the versatile X-15E provides a wide range of options for any environment. The new model features selectable gamma curves,
- Features and benefits of the NEOVO X 15 E monitor:
 - LED backlighting and 1920 x 1080 /1280 x 1024 / 1024 x 768 resolution,
 - NeoV™ optical glass and durable metal casing provide superior clarity and protection,
 - · VA panel technology ensures accurate colors and offers high contrast ratio with wide viewing angles,
 - Anti-Burn-inTM technology prevents ghosting in the image,
 - Clear dynamic contrast ratio of 20.000.000:1.
 - Gamma correction for improved clarity and color quality,
 - PiP/PbP functions allow simultaneous viewing of images from multiple sources,
 - · Image enhancement: deinterlacing/noise reduction,
 - Flicker-free display Flicker-free display technology reduces eye fatigue during prolonged use,
 - EcoSmart sensor detects ambient light conditions and automatically adjusts brightness levels,
 - · Versatile connectivity: DisplayPort, HDMI, DVI, VGA,
 - Built-in speakers,
 - · High-quality panel for high reliability and long product life,
 - VESA standard wall mounting kit,
 - · Available colors: black, white,
 - · Designed and developed for 24/7 continuous operation,
- Specifications:
 - Matrix:
 - Panel type: LED-Backlit TFT LCD (VA Technology),
 - Diagonal: 15.0",
 - Max. Resolution: XGA 1024 x 768,
 - Spot: 0.297 mm,
 - Brightness: 300 cd/m2.
 - Contrast ratio 20,000,000:1 (DCR),
 - Viewing angles (Pos/Pio): 176°/176°,
 - Color gamut: 16.2 M,
 - Response time: 5 ms,
 - Frequency (Pos/Pio):
 - Horizontal: 24 kHz 83 kHz,
 - Vertical: 50 Hz 75 Hz,
 - Inputs:
 - VGA: 15-Pin D-Sub x 1,
 - DVI: 24-Pin DVI-D x 1,
 - HDMI: 1,4 x 1,
 - DisplayPort: DisplayPort x 1,
 - · Audio:
 - Input: Stereo Audio Jack (3.5mm),
 - Speakers: 2W X 2,
 - · Power supply:
 - Power supply: External,
 - Current: DC 12V, 1.49 A,
 - Power consumption:
 - Power consumption: 10W (on),
 - Sleep mode: < 0.5W,
 - Off: < 0.3W,
 - NeoV[™] optical filter:
 - Thickness: 3.0 mm (0.12"),
 - Reflectance ratio: < 1%,
 - Transparency factor: > 97%,
 - Surface hardness: 9H.
 - Operating Conditions:
 - Temperature: 0°C-40°C (32°F-104°F),
 - Humidity: 10%~90% (non-condensing),
 - Storage Conditions:
 - Temperature: -20°C-60°C (-4°F-140°F),
 - Humidity: 5%~95% (non-condensing),
 - VESA FPMPMI: Yes (100 x 100 mm & 75 x 75 mm),
 - Stand: ■ Tilt: 0° to 20°,
 - Security:
 - Kensington[™] security slot: Yes,
 - Dimensions:
 - Product with stand (W x H x D): 380.0 x 359.0 x 155.0 mm (15.0" x 14.1" x 6.1"),
 - Product without base (W x H x D): 380.0 x 315.0 x 53.5 mm (15.0" x 14.1" x 2.1"),
 - Package (W x H x D): 470.0 x 460.0 x 199.0 mm (18.5" x 18.1" x 7.8"),
 - Weight:
 - Monitor without stand: 4.2 kg (9.3 lb),
 - Monitor with stand: 4.6 kg (10.1 lb),
 - Monitor with packaging: 5.9 kg (12.9 lb),
 - Regulatory Compliance:
 - Declarations and Directives: CE, LVD, WEEE, RoHS, REACH, EAC,
 - Power supply certifications: Delta /ADP-40DD-B: CE, cUL/UL, RCM, WEEE, KCC, BSMI, EAC,
 - Accessories:
 - Supplied with the monitor; power adapter, power cord, VGA cable, audio cable, guick start guide, warranty card,
 - Optional accessories (at extra charge):
 - Table mount: DMC-01, DMC-02D, DMS-01D, DMS-01Q, ES-02,
 - Ceiling mount (horizontal only): CMP-01 + WMK-03,
 - Wall mounts (horizontal only): WMA-01, WMK-01, WMK-03, PMK-01,
- · Has a current Technical Passport issued,
- · Warranty 36 months.



www.praiston.pl